





MM EFF : MULTI-MASTER, 4 flute, FEEDMILL, interchangeable solid carbide heads. Used for milling at very high feed and small D.O.



Designation	D	Z	ap	Ts	D2	l	a°	r	fz(min)	fz(max)	Grade
MM EFF080T3R1.62-4T05	8.00	4	0.40	T05	7.50	10.00	7	1.62	0.12	0.48	IC903
MM EFF100T4R2.01-4T06	10.00	4	0.50	T06	9.50	13.00	7	2.01	0.16	0.57	IC903
MM EFF120T4R1.8-4T08H	12.00	4	0.60	T08	11.50	16.50	7	1.80	0.16	0.67	IC908
MM EFF120T4R2.47-4T08	12.00	4	0.60	T08	11.50	16.50	7	2.47	0.16	0.67	IC903
MM EFF127T4R2.59-4T08	12.70	4	0.60	T08	12.20	16.50	7	2.59	0.16	0.67	IC903
MM EFF160T5R2.2-4T10H	16.00	4	0.80	T10	15.40	20.50	7	2.20	0.20	0.75	IC908
MM EFF160T5R3.25-4T10	16.00	4	0.80	T10	15.40	20.50	7	3.25	0.20	0.75	IC903
MM EFF200T6R4.02-4T12	20.00	4	1.00	T12	18.45	25.50	7	4.02	0.20	0.90	IC903
MM EFF250A7R3.1-6T15	25.00	6	1.20	T15	23.90	25.00	7	3.10	0.25	1.00	IC903
MM EFF254A7R3.63-6T15	25.40	6	1.20	T15	23.90	25.00	7	3.10	0.25	1.00	IC903

For Clamping keys (should be ordered separately), tightening torques and clamping instructions, click on "More Info".

Do not apply lubricant to the threaded connection.