





ECC-A-2 : 2 flute, 30° helix medium length solid carbide slot / drill endmills with chamfered corners.



Designation	D	d	Flute	ap	L	Rd?/b>	Shank	Ch	fz(min)	fz(max)	Grade
ECC020B07-2C03	2.00	3.00	2	7.00	38.00	5.0	C	0.10	0.01	0.03	IC300IC900
ECC025A07-2C03	2.50	3.00	2	7.00	38.00	5.0	C	0.10	0.01	0.03	IC300IC900
ECC030A10-2C03	3.00	3.00	2	10.00	38.00	5.0	C	0.10	0.01	0.04	IC300IC900
ECC035A12-2C04	3.50	4.00	2	12.00	50.00	5.0	C	0.10	0.01	0.04	IC300IC900
ECC040A12-2C04	4.00	4.00	2	12.00	50.00	5.0	C	0.15	0.02	0.05	IC300IC900
ECC050A14-2C05	5.00	5.00	2	14.00	50.00	5.0	C	0.15	0.02	0.06	IC300IC900
ECC060A16-2C06	6.00	6.00	2	16.00	57.00	5.0	C	0.15	0.03	0.07	IC300IC900
ECC060A16-2W06	6.00	6.00	2	16.00	57.00	5.0	W	0.15	0.03	0.07	IC900
ECC080A20-2C08	8.00	8.00	2	20.00	63.00	5.0	C	0.15	0.03	0.09	IC300IC900
ECC080A20-2W08	8.00	8.00	2	20.00	63.00	5.0	W	0.15	0.03	0.09	IC300
ECC100A22-2C10	10.00	10.00	2	22.00	72.00	5.0	C	0.25	0.03	0.10	IC300IC900
ECC100A22-2W10	10.00	10.00	2	22.00	72.00	5.0	W	0.25	0.03	0.10	IC900
ECC120A25-2C12	12.00	12.00	2	25.00	83.00	5.0	C	0.25	0.04	0.11	IC300IC900
ECC120A25-2W12	12.00	12.00	2	25.00	83.00	5.0	W	0.25	0.04	0.11	IC300IC900
ECC160A32-2C16	16.00	16.00	2	32.00	92.00	5.0	C	0.25	0.05	0.13	IC300IC900
ECC200A38-2C20	20.00	20.00	2	38.00	104.00	5.0	C	0.25	0.05	0.13	IC300IC900
ECC200A38-2W20	20.00	20.00	2	38.00	104.00	5.0	W	0.25	0.05	0.13	IC300IC900

