







MM EC-8/MM EC-10 : MULTI-MASTER 8, 10 flute, 30° and 45° helix, interchangeable solid carbide endmill heads with various corner



Designation	D	Flute	ap	r	Ts	D2	l	Ha°	Rd°	Coolant	fz(min)	fz(max)	Grade
MM EC160A12R0.5-8T10	16.00	8	12.00	0.50	T10	15.20	20.50	30.0	5.0	Y	0.05	0.13	IC908
MM EC160A12R0.5-8T10H	16.00	8	12.00	0.50	T10	15.20	20.50	30.0	5.0	-	0.05	0.13	IC908
MM EC160A12R1.0-8T10	16.00	8	12.00	1.00	T10	15.20	20.50	30.0	5.0	-	0.05	0.13	IC908
MM EC160A12R1.6-8T10	16.00	8	12.00	1.60	T10	15.20	20.50	30.0	5.0	-	0.05	0.13	IC908
MM EC160A12R2.0-8T10	16.00	8	12.00	2.00	T10	15.20	20.50	30.0	5.0	-	0.05	0.13	IC908
MM EC160B12R0.5-8T10	16.00	8	12.00	0.50	T10	15.20	20.50	45.0	5.0	-	0.05	0.13	IC908
MM EC160B12R1.0-8T10	16.00	8	12.00	1.00	T10	15.20	20.50	45.0	5.0	-	0.05	0.13	IC908
MM EC160B12R1.6-8T10	16.00	8	12.00	1.60	T10	15.20	20.50	45.0	5.0	-	0.05	0.13	IC908
MM EC160B12R2.0-8T10	16.00	8	12.00	2.00	T10	15.20	20.50	45.0	5.0	-	0.05	0.13	IC908
MM EC200A15R1.0-10T12	20.00	10	15.00	1.00	T12	18.30	25.50	30.0	3.0	-	0.05	0.13	IC908
MM EC200A15R2.0-10T12	20.00	10	15.00	2.00	T12	18.30	25.50	30.0	3.0	-	0.05	0.13	IC908
MM EC250A22R0.8-10T15	25.00	10	22.00	0.80	T15	23.90	37.00	30.0	3.0	-	0.05	0.13	IC908

For Clamping keys (should be ordered separately), tightening torques and clamping instructions, click on "More Info".

Do not apply lubricant to the threaded connection.