




**EC-H4XL-CFR (Relieved neck)** : 4 flute long endmills with different helix (35° & 37°) and variable pitch for chatter dampening with Used for very high material removal rates roughing and finishing operations. Full slot milling-up to 2XD.



Designation	D	d	ap	H	L	Flute	r	Rd°	Shank	fz(min)	fz(max)	Grade
EC-H4XL 06-12/25C06CFR.2	6.00	6.00	12.00	25.00	61.00	4	0.20	5.0	C	0.03	0.06	IC900
EC-H4XL 06-12/25W06CFR.2	6.00	6.00	12.00	25.00	61.00	4	0.20	5.0	W	0.03	0.06	IC900
EC-H4XL 08-16/32C08CFR.4	8.00	8.00	16.00	32.00	68.00	4	0.40	5.0	C	0.03	0.08	IC900
EC-H4XL 08-16/32W08CFR.4	8.00	8.00	16.00	32.00	68.00	4	0.40	5.0	W	0.03	0.08	IC900
EC-H4XL 10-20/40C10CFR.5	10.00	10.00	20.00	40.00	80.00	4	0.50	5.0	C	0.03	0.09	IC900
EC-H4XL 10-20/40W10CFR.5	10.00	10.00	20.00	40.00	80.00	4	0.50	5.0	W	0.03	0.09	IC900
EC-H4XL 12-24/50C12CFR.6	12.00	12.00	24.00	50.00	95.00	4	0.60	5.0	C	0.04	0.10	IC900
EC-H4XL 12-24/50W12CFR.6	12.00	12.00	24.00	50.00	95.00	4	0.60	5.0	W	0.04	0.10	IC900
EC-H4XL 16-32/64C16CFR.8	16.00	16.00	32.00	64.00	115.00	4	0.80	5.0	C	0.05	0.11	IC900
EC-H4XL 16-32/64W16CFR.8	16.00	16.00	32.00	64.00	115.00	4	0.80	5.0	W	0.05	0.11	IC900
EC-H4XL 20-40/75C20CFR1.0	20.00	20.00	40.00	75.00	125.00	4	1.00	5.0	C	0.05	0.11	IC900
EC-H4XL 20-40/75W20CFR1.0	20.00	20.00	40.00	75.00	125.00	4	1.00	5.0	W	0.05	0.11	IC900