






MT-UN-MM : Carbide milling heads with a threaded (MULTI-MASTER) connection, for internal UN thread profile.



Application:
General Engineering



Application: General engineering



Designation	TPI	UNC	UNF	UNEF	D	Flute	ap	l1	Ts	Grade
MT 10D6 24UN-MMT05	24.0	-	-	9/16-5/8	10.00	5	5.30	13.35	T05	IC908
MT 10D6 20UN-MMT05	20.0	-	1/2	-	10.00	4	5.10	13.35	T05	IC908
MT 10D5 18UN-MMT05	18.0	-	9/16-5/8	1 1/8-1 5/8	10.00	4	5.60	13.35	T05	IC908
MT 12D8 16UN-MMT06	16.0	-	3/4	-	12.00	4	8.00	17.05	T06	IC908
MT 16E12 14UN-MMT08	14.0	-	7/8	-	16.00	5	12.70	20.85	T08	IC908
MT 16E12 12UN-MMT08	12.0	-	1-1 1/2	-	16.00	5	12.70	20.85	T08	IC908
MT 15D12 10UN-MMT08	10.0	3/4	-	-	15.30	4	12.70	20.85	T08	IC908
MT 16C11 9UN-MMT08	9.0	7/8	-	-	16.00	3	11.30	20.85	T08	IC908

For shanks, see pages...

For clamping keys (should be ordered separately), tightening torques and clamping instructions, see page...

Do not apply lubricant to the threaded connection