





GHMR/L : CUT-GRIP toolholders for shallow radial and axial grooving. Light turning, small depth of cut ($a_p=0.1-0.5$ mm), and small



Right-hand shown



Designation	W max	Tmax-r	Tmax-a	h	b	l1	l2	f	h4
GHML 12	4.00	4.80	4.80	12.0	12.0	110.00	25.0	10.8	4.0
GHMR 12	4.80	4.80	4.80	12.0	12.0	110.00	25.0	10.8	4.0
GHML 16	4.80	4.80	4.80	16.0	16.0	115.00	25.0	14.5	-
GHMR 16	4.80	4.80	4.80	16.0	16.0	115.00	25.0	14.5	-
GHML 16-3 ST	5.00	4.80	4.80	16.0	16.0	78.00	25.0	15.0	-
GHMR 16-3 ST	5.00	4.80	4.80	16.0	16.0	78.00	25.0	15.0	-
GHML 20	6.40	4.80	4.80	20.0	20.0	125.00	25.0	18.5	-
GHMR 20	6.40	4.80	4.80	20.0	20.0	125.00	25.0	18.5	-
GHML 25	6.40	4.80	4.80	25.0	25.0	140.00	25.0	23.5	-
GHMR 25	6.40	4.80	4.80	25.0	25.0	140.00	25.0	23.5	-
GHML 32	6.40	4.80	4.80	32.0	32.0	150.00	25.0	30.2	-
GHMR 32	6.40	4.80	4.80	32.0	32.0	150.00	25.0	30.2	-

For insert clamping instructions, click on "More Info".