





C#-HELIR/L : HELI-GRIP external grooving turning and parting toolholders, with CAMFIX (ISO 26623-1 standard) exchangeable, t



Left-hand shown



Designation	W min	W max	f	l1	SS	D max
C4 HELIL 3T20	3.00	3.18	20.0	65.00	40	40.0
C4 HELIR 3T20	3.00	3.18	20.0	65.00	40	40.0
C5 HELIL 3T20	3.00	3.18	25.3	65.00	50	40.0
C5 HELIR 3T20	3.00	3.18	25.3	65.00	50	40.0
C6 HELIL 3T20	3.00	3.18	31.8	65.00	63	40.0
C6 HELIR 3T20	3.00	3.18	31.8	65.00	63	40.0
C4 HELIL 4T25	4.00	4.76	19.6	70.00	40	50.0
C4 HELIR 4T25	4.00	4.76	19.6	70.00	40	50.0
C5 HELIL 4T25	4.00	4.76	24.9	70.00	50	50.0
C5 HELIR 4T25	4.00	4.76	24.9	70.00	50	50.0
C6 HELIL 4T25	4.00	4.76	31.4	70.00	63	50.0
C6 HELIR 4T25	4.00	4.76	31.4	70.00	63	50.0
C5 HELIL 5T25	5.00	5.00	24.4	70.00	50	50.0
C5 HELIR 5T25	5.00	5.00	24.4	70.00	50	50.0
C6 HELIL 5T25	5.00	5.00	30.9	70.00	63	50.0
C6 HELIR 5T25	5.00	5.00	30.9	70.00	63	50.0
C6 HELIL 6T30	6.00	6.35	30.4	85.00	63	60.0
C6 HELIR 6T30	6.00	6.35	30.4	85.00	63	60.0

The depth of cut (T) for grooving is limited by the part diameter D. For grooving depth capacity, click on "More Info"